

ASME B36.19: Specification for stainless steel pipes

DN	NPS	OD	Sch5S	Sch10S	Sch40S	Sch80S	Sch160S
6	1/8	10.3		1.24	1.73	2.41	3.15
8	1/4	13.7		1.65	2.24	3.02	3.68
10	3/8	17.1		1.65	2.31	3.2	4.01
15	1/2	21.3	1.65	2.11	2.77	3.73	4.78
20	3/4	26.7	1.65	2.11	2.87	3.91	5.56
25	1	33.4	1.65	2.77	3.38	4.55	6.35
32	1 1/4	42.2	1.65	2.77	3.56	4.85	6.35
40	1 1/2	48.3	1.65	2.77	3.68	5.08	7.14
50	2	60.3	1.65	2.77	3.91	5.54	8.74
65	2 1/2	73	2.11	3.05	5.16	7.01	9.52
80	3	88.9	2.11	3.05	5.49	7.62	11.13
90	3 1/2	101.6	2.11	3.05	5.74	8.08	
100	4	114.3	2.11	3.05	6.02	8.56	13.49
125	5	141.3	2.77	3.40	6.55	9.53	15.88
150	6	168.3	2.77	3.40	7.11	10.97	18.26
200	8	219.1	2.77	3.76	8.18	12.7	
250	10	273.1	3.40	4.19	9.27	12.7	
300	12	323.9	3.96	4.57	9.53	12.7	
350	14	355.6	3.96	4.78	9.53	12.7	
400	16	406.4	4.19	4.78	9.53	12.7	
450	18	457	4.19	4.78	9.53	12.7	
500	20	508	4.78	5.54	9.53	12.7	
550	22	559	4.78	5.54			
600	24	610	5.54	6.35	9.53	12.7	
650	26	660					
700	28	711					
750	30	762	6.35	7.92			
800	32	812.8					
850	34	863.6					
900	36	914.4					
	38	965.2					
1000	40	1016					
1050	42	1066.8					
1100	44	1117.6					
	46	1168.4					
1200	48	1219.2					